

# COAXIAL CONNECTOR, N, 50 Ohm, Straight bulkhead cable jack (female)

24\_N-50-7-8/133\_N

## Properties

- Screwed coupling mechanism for sturdy and reliable connection
- IP rating (interface, mated) IP67
- Interface dimensions according IEC/MIL



## Product configuration

Gender	Standard
jack	IEC 61169-16_MIL-STD-348A/304_CECC 22210

## Interface and material data

Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating

## Electrical data

Impedance	50 $\Omega$
Interface frequency	11 GHz

## Mechanical data

Weight	0.0525 kg
Mating cycles	500
Cable entry centre contact	soldered
Cable entry outer contact	clamped

## Environmental data

Operation temperature	-65 °C ... 165°C
-----------------------	------------------

**COAXIAL CONNECTOR, N, 50 Ohm, Straight bulkhead cable jack (female)**

24\_N-50-7-8/133\_N

Ordering Information Table		
Item number	Item description	Packaging type
22542323	24_N-50-7-8/133_NE	Single

Suitable cables	
Cable group	U32 - 7 mm / 50 Ohm
	U29 - 7 mm / 50 Ohm
Suitable cables	GX_07272
	RG_214_/U
	RG_213_/U

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P2605 / Date of publication: 25.11.2023 / uncontrolled copy