Data Sheet

HUBER+SUHNER

Coaxial Panel Connector 23_BNC-50-0-16/133_N

Description

Straight panel receptacle jack, flange mount

Interface standards IEC 60169-8_MIL-STD-348A/301_CECC 22120



Technical Data

| Electrical Data Impedance Interface frequency max. | 50 Ω 4 GHz |
|--|-------------------------------|
| Mechanical Data Number of matings Weight | 500 0.0101 kg |
| Environmental Data Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | -65 °C to 165 °C compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|------------------------|-----------------------------------|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |

Related Documents

| Outline drawing | DOU-00010119 |
|-------------------|--------------|
| Catalogue drawing | DCA-00010121 |
| Mounting hole | DOU-00009051 |

Ordering Information

Bulk 100 pcs package Single package 23_BNC-50-0-16/133_NH 23_BNC-50-0-16/133_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.