Data Sheet

Coaxial Panel Connector 23_N-50-0-1/133_N

Description

Straight panel receptacle jack, flange mount

Interface standards IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data Impedance Interface frequency max.	50 Ω 11 GHz
Mechanical Data Number of matings Weight	500 0.0301 kg
Environmental Data Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102)	-65 °C to 165 °C compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Bronze	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00010382
Catalogue drawing	DCA-00010384
Mounting hole	DOU-00010096

Ordering Information

Single package

23_N-50-0-1/133_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

