

Coaxial Cable Connector 11_UHF-0-7-17/033_-

Description

Straight cable plug

Interface standards
IEC 60169-12



Technical Data

Electrical Data

Impedance other Ω
Interface frequency max. 0.2 GHz

Mechanical Data

Centre contact crimped
Outer contact crimped
Weight 0.0238 kg

Environmental Data

Operating temperature -55 °C to 165 °C
2011/65/EU (RoHS - including
2015/863 and 2017/2102) compliant

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|-------------------|-----------------------|
| Centre contact | Brass | Silver Plating |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PSU (Polysulfone) | |
| Coupling nut | Brass | SUCOPLATE (R) Plating |
| Crimp ferrule | Copper | SUCOPLATE (R) Plating |

Related Documents

Outline drawing DOU-00181576
Catalogue drawing DCA-00045040
Assembly instruction DOC-0000201061

Ordering Information

Single package 11_UHF-0-7-17/033_-E

Additional Information

Suitable cables RG_213_/U, GX_07272, G_07262, G_07272, RADOX_RF_213