Data Sheet

Coaxial PCB Connector 86_CT-0-1-1/111_N

Description

Right angle PCB cable terminator

Interface Standards

HUBER+SUHNER



Technical Data

Electrical Data		
Impedance	other Ω	
Mechanical Data		
Board mounting type	through holes	
Weight	0.0003 kg	
Environmental Data		
Operating temperature	-65 °C to 165 °C	
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant	
Material Data		
Piece Parts	Material	Surface Plating
Centre contact	Brass	SUCOPRO Plating
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / PTFE	
Related Documents		
Outline drawing	DOU-00012736	
Catalogue drawing	DCA-00012738	
Assembly instruction	DOC-0000192830	
Mounting hole	DOU-00012739	
Ordering Information		
Bulk 100 pcs package	86_CT-0-1-1/111_NH	
Single package	86_CT-0-1-1/111_NE	
Bomarka		

Remarks

PCB connector without stand-offs, suitable for cable group U1(RG_178_B/U), cable entry: soldered

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.